

Armrests

- Stable, ergonomically shaped armrests with curved support surface (350 x 120 mm)
- Height-adjustable and equipped with a ball joint for 360-degree rotation
- Designed for personalized adjustment to the surgeon
- Optionally available with one-hand release
- Optionally available with linear guide and one-hand release



Chassis

- Powder-coated tubular steel frame with sanitary, scratch-resistant high-shine plastic cover panels
- 4 high-quality, smooth-running double castors
- Central braking system effective on 4 castors
- Integrated foot keypad panel for seat height adjustment
- Power supply-independent battery box with emergency stop button



Technical specifications

Lifting column

- Drive 3,000 N (IPX4)
- Lifting height 200 mm

Chassis

- L x W (incl. braking system/foot keypad) 640 x 600 mm
- Castors ø 100 mm
- Central brake acting on all four castors
- Emergency stop button

Battery unit

- Battery box with 2 batteries (lead-gel), pollution free, maintenance-free, cadmium-free 2 x 12 V, 7.2 Ah
- Universal battery charger: Input: 100 – 240 V
Output: 30 V

Seating systems:

Formed seat | Comfort

- Min. sitting height 530 mm | 550 mm
- Max. sitting height 730 mm | 750 mm
- Seat angle adjustments +6°/-5° | +5°/-5°
- Back angle adjustments +5°/-18° | +5°/-25°

Weight

45 kg

Max. load

150 kg

Subject to technical modifications.

Technical dimensions

Seating system Formed seat

Minimum



Specifications in mm

Maximum



Seating system Comfort

Minimum



Maximum

