

## APM 440 plus

## **MATTRESS SPECIFICATIONS**



PRESSURE ULCER GRADE: II 🔵 III 🔵 IV

MAX. PATIENT WEIGHT: 230 kg ITEM NO: 991500X

**CONTROL UNIT:** 

Measurements: 39 x 21 x 12 cm

Weight: 5 ka

2 membrane compressors, digital control with pressure sensor, alternating pressure, static mode, care mode, 3 time cycles (5/10/15 min.), automatic key lock function (3 min.), low pressure alarm, power failure alarm, set-up memory function

**MATTRESS:** 

200 x 88 x 22 cm Measurements:

(inflated incl. 2 cm matress base)

Weight: 12.5 kg

20 cells, 3 head cells static, non-bending connecting tubes (incl. transportation safety lock), self-closing connection valves, CPR emergency ventilation

**MATERIALS:** 

Cells: nylon with polyurethane coating

bi-elastic PU/PES, breathable, slip-retardant Cover: Base: nylon cover with integrated pocket for 2 cm base

mattress

## INCLUDED IN DELIVERY:

transport bag for mattress and control unit, foam mattress base with nylon cover

## THE APM 440 PLUS ALTERNATING PRESSURE SYSTEM IS SUITED FOR THE TREATMENT OF PRESSURE ULCERS UP TO GRADE IV (AC-CORDING TO EPUAP).

The control unit is equipped with a digital sensor control, which regulates the inner pressure of the mattress, creating a perfect surface pressure. The use of two compressors quarantees fast inflation and operation of the mattress. Adjustment is accomplished with the aid of a touch pad surface, equipped with visually easy to comprehend pictograms. The result is a quick and easy operation.

- · bi-elastic, breathable PU/PES cover, non-bending connecting tubes, connection coupling with transportation safety lock, external CPR valve
- · sensor operated pressure management, between cycles switch off, automatic key lock, alternating pressure, static and care mode, 3 time cycles with 5/10/15 minute selection
- · holds up to 230 kg patient weight



