

# Technical specifications



## Chassis

- Outside length 900 mm
- Outside width 662 mm
- Brake system acting on all four castors
- Directionally guided steering ("Steering Guide"), easily activated at the push of a button
- Castor diameter, electr. conductive  $\varnothing$  150/100 mm
- Foot control element with joystick (total, head, back, Trendelenburg up/down)
- Emergency stop button
- Optional push-aid (**e-drive**)
- With equipotential bonding connection
- Abrasion-resistant corner guards (orange) made of synthetic rubber

## Trendelenburg/Reverse Trendelenburg



## Upper frame

- 4-part support frame (head, back, seat, leg part)
- Removable upholstery 40 mm
- Width of upholstery 650 mm
- Standard stainless steel side rails on both sides 25 x 10 mm
- Width incl. norm rails 700 mm
- Length 1,780 – 1,900 mm

	Angle	Dimensions (L x W)
• Head part	-31°/+22°	255 x 245 mm
• Back part	0°/+75°	540 x 650 mm
• Seat part	-6°/+26°	450 x 650 mm
• Leg part	0°/-78°	510 x 610 mm
• Height adjustment		640 – 900 mm
• Entry height		580 mm
• Legroom		470 – 730 mm
• Trendelenburg -26°/Reverse Trendelenburg +6°		

## Back part/leg part



## Electrical control

### Manual keypad

- Memory controller with 10 buttons for head, back, seat, leg part – total up/down; 2 buttons for directionally guided steering, 1 button for electronic brake, 1 easy entry button, memory button, on-off button, auto-run function
- 5 freely programmable memory positions
- Visual battery level indicator

### Foot control element

- Foot control element 2 joysticks plus activation switch
- Optional push-aid (**e-drive**)

### Electric drives

- Head, back, seat, leg part, total up/down
- Trendelenburg/Reverse Trendelenburg

## Height adjustment



