

Are You Ready for DICOM Integration?



Medical-Grade Digital Video Recorder

UR-4MD

Designed for the mission-critical OR environment


Full HD 1920 × 1080 Video and photo recording Advanced
Reliability
w/ Fail-safe recording

DICOM Gateway* Modality Worklist support

3.5 Inch Built-in LCD display Simultaneous recording USB & IHDD

Plug & Play Automatic configuration

* DICOM Gateway is an optional upgrade.



Key Features

- Crystal-clear, full-HD 1920 × 1080, video and photo recording
- Built-in 3.5-inch LCD display for live view / playback / navigation
- Auto signal detection and auto resolution setting
- Safe recording to iHDD, USB devices and network drive simultaneously
- Networking (FTP and CIFS) RJ45 10/100/1000 Ethernet
- Remote control via camera or foot-pedal¹
- Feeding patient data via keyboard or barcode¹
- PACS connectivity²: DICOM storage and MWL support*
- Medical standards Specifications

UR-4MD is TEAC's latest high-definition medical video recorder designed for quick setup and ease of use, yet includes a robust list of features and capabilities. With auto-sensing video connections and automatic video resolution detection, setup is quick and easy.

The front control panel allows users to intuitively record videos and photos in crystal-clear HD. A built-in hard drive is included for reliable recording and data back-up and users can also simultaneously record to USB memory and USB hard drives to archive, share and play back on other devices and locations. UR-4MD is also network capable. With an optional upgrade, DICOM integration is made easy.

¹Optional device(s) required. ²Upgrade available.

Storage ar	nd Dienlay			
	ilu Dispiay			
Recordable devices		USB flash drive, USB hard drive		
		Internal hard drive (optionally 500 GB or 1 TB)		
Built-in LCD display		3.5 inch, full-color		
Recording format (FAT32)		Compression	File format	
Photo		JPEG, DICOM	JPG, DCM	
Video		MPEG-4 AVC/H.264	MOV	
Input/Outp	put			
	Input/ Output	SDI (BNC) ×1	3G/HD-SDI: 1080p/1080i/720p, SD-SDI: 480i/576i	
V:		DVI (Single Link) ×1	High-definition	
Video		S-Video ×1	NTSC, PAL	
		Composite (BNC) ×1	NTSC, PAL	
-	Output	SDI Thru ×1		
	Input/	SDI (BNC) ×1	* SDI video output terminal used in common	
Audio	Output	Stereo mini jack ×1	LINE	
	Input	Stereo mini jack ×1	MIC	
Other interfaces		RJ-45 (10BASE-T / 100BASE-TX / 1000BASE-T) ×1		
		USB 2.0 Type A ×3	2 front connectors for recordable devices	
			1 rear connector for optional accessories	
		USB 2.0 Type B ×1	1 rear connector for accessing the internal hard drive (on UR-4MD)	
		Stereo mini jack ×3	For external trigger	
General		·		
Power supply		AC 100-240 V, 50/60 Hz		
Dimensions (W×D×H)		Approx. 211 mm × 235 mm × 89 mm		
Weight		Approx. 2.6 kg		
Certifications		Safety UL 60601-2003, CE, IEC 60601-1, CSA 60601-1, EN 60601-1		
		EMC IEC 60601-1-2, EN 60601-1-2, ICES-003, FCC Class B		
Category		FDA Class 1, ANVISA, RoHS, CCC		
What's in the box		TEAC UR-4MD, Power cords, Cable clamp, Owner's manuals		
Optional accessories		Remote control unit, Foot-switch, Keyboard, Barcode/Card Reader		

Blu-ray™ Disc, Blu-ray™ and the Blu-ray™ Disc logo are trademarks of Blu-ray™ Disc Association. Other company names, product names and logos in this document are the trademarks or registered trademarks of their respective owners. Features and specifications are subject to change without notice.

Recording Times (for a 500 GB hard drive)

HD definition 1920 x 1080					
12 Mbit/s	18 Mbit/s	24 Mbit/s			
90 hours	60 hours	45 hours			
SD definition 640 × 480					
5 Mbit/s	8 Mbit/s	10 Mbit/s			
180 hours	135 hours	100 hours			

Times are approximate.

UR-4MD Digital Video Recorder





Rear view

TEAC EUROPE GmbH

Bahnstrasse 12, 65205 Wiesbaden-Erbenheim

Germany

Tel.: +49 611-7158-349 Email: info@teac.eu

Fax: +49 611-7158-392 https://teac.eu/en/